

Product Specifications



P550406

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	107 mm (4.21 inch)
Thread Size	M26 x 1.5
Length	153 mm (6.02 inch)
Gasket OD	73 mm (2.87 inch)
Gasket ID	56 mm (2.20 inch)
Efficiency 50%	16 micron
Efficiency Test Std	SAE J806
Anti-Drainback Valve	Yes
Bypass Valve	Yes

Bypass Valve Setting LR	1.7 bar (25 psi)
Bypass Valve Setting HR	2.1 bar (30 psi)
Media Type	Cellulose
Collapse Burst	6.9 bar (100 psi)
Туре	Full-Flow
Style	Spin-On
Primary Application	HINO 156071480

Other Information

UPC Code	742330106594	

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.